

















## SELF-WELDING BELTS "TM BELT" MADE IN ITALY

Colour	Transparent		Transparent		Green		Green		Transparent		Transparent		Green		Green	
Shore	85		85		85		85		85		85		85		85	
Use Temperature	-30°C+80°C		-30°C+80°C		-30°C+80°C		-30°C+80°C		-30°C+80°C		-30°C+80°C		-30°C+80°C		-30°C+80°C	
Belt Surface	Smooth		Smooth		Smooth		Smooth		Honeycomb		Honeycomb		Honeycomb		Honeycomb	
Reinforce	No		Yes		No		Yes		No		Yes		No		Yes	
																
Section	Max Charge (daN)	PMD	Max Charge (daN)	PMD	Max Charge (daN)	PMD	Max Charge (daN)	PMD	Max Charge (daN)	PMD	Max Charge (daN)	PMD	Max Charge (daN)	PMD	Max Charge (daN)	PMD
A (13 X 8) **	29	95	29	100	29	95	29	100	29	95	29	100	29	95	29	100
B (17 X 11) **	52	120	52	140	52	120	52	140	52	120	52	140	52	120	52	140
C (22 X 14) **	86	160	86	180	86	160	86	180	86	160	86	180	86	160	86	180

\*\* ROLLS of 30 MT

Colour	Transparent		Transparent		Green		Green		Transparent		Transparent		Green		Green	
Shore	85		85		85		85		85		85		85		85	
Use Temperature	-30°C+80°C		-30°C+80°C		-30°C+80°C		-30°C+80°C		-30°C+80°C		-30°C+80°C		-30°C+80°C		-30°C+80°C	
Belt Surface	Crested		Crested		Crested		Crested		Crested		Crested		Crested		Crested	
Reinforce	No		Yes		No		Yes		No		Yes		No		Yes	
																
Section	Max Charge (daN)	PMD	Max Charge (daN)	PMD	Max Charge (daN)	PMD	Max Charge (daN)	PMD	Max Charge (daN)	PMD	Max Charge (daN)	PMD	Max Charge (daN)	PMD	Max Charge (daN)	PMD
B (17 X 19) **	76	190	76	190	76	190	76	190	70	180	76	180	70	180	76	180
C (22 X 25) **	131	240	131	240	131	240	131	240	117	220	131	220	117	220	131	220

\*\* Section B: ROLLS of 40 MT

\*\* Section C: ROLLS of 30 MT

PMD – Pulley Minimum Diameter in mm

Color		Transparent		Transparent		Green		Green	
Shore		85		85		88		88	
Use Temperature		-30°C+80°C		-30°C+80°C		-30°C+80°C		-30°C+80°C	
Belt Surface		Smooth		Smooth		Rough and Smooth		Rough and Smooth	
Reinforce		No		Yes		No		Yes	
									
Diameter	Rolls in meters	Max Charge (daN)	PMD	Max Charge (daN)	PMD	Max Charge (daN)	PMD	Max Charge (daN)	PMD
2	200	1	15	NF	NF	1,2	15	NF	NF
3	200	2	20	NF	NF	2,6	20	NF	NF
4	200	3,8	35	NF	NF	4,6	35	NF	NF
5	100	5,8	50	NF	NF	7	50	NF	NF
6	100	8,4	60	10	60	10	60	10,2	60
7	100	11,6	70	13,8	70	13,8	70	13,8	70
8	100	15	80	18	80	18	80	18	80
9	100	19	90	23	90	23	90	23	90
10	50	23,6	100	28	100	28	100	28	100
12	50	34	120	40	120	40	120	40	120
15	50	53	150	63	150	63	150	63	150
18	50	76	180	91	180	91	180	91	180
20	50	94	200	113	200	113	220	113	220

PMD – Pulley Minimum Diameter in mm

NOTES: FOR COLOURS AND SHORES DIFFERENT FROM THE CATALOGUE, PLEASE CONTACT OUR SALES DEPARTMENT



**ALLUMINIUM PLIERS**  
*Clamp Aluminium*



**WELDER**  
*Schweißer*



**SCISSORS**  
*Schere*