

# INCHIOSTRI

INKS

TINTAS





## Scheda Tecnica Technical Data Sheet Ficha Tecnica

### JET INK BLACK TINTA NEGRA

#### TECHNICAL CHARACTERISTICS / CARACTERISTICAS TECNICAS

| Colour ref. No   | BLACK      |  |  |  |  |  |
|--|------------|--|--|--|--|--|
| Viscosity BROOKFIELD „SC4-18, rpm 200 -60” (cps, 25°C) | 2,1+/-0,3  |  |  |  |  |  |
| pH   | 7 +/-0,5   |  |  |  |  |  |
| Tension surface mN/m                                   | 38 +/- 0,5 |  |  |  |  |  |
|  |            |  |  |  |  |  |
|  |            |  |  |  |  |  |
|  |            |  |  |  |  |  |

#### HANDLING INSTRUCTIONS / CONDICIONES DE UTILIZO

Store between +5 °C and +35 °C.

Do not expose to temperatures below 5°C and over 35°C. .

#### PACKING / CONFECCION

5-kg net plastic drums.  
10-kg net plastic drums.  
20-kg net plastic drums.  
50-kg net plastic drums.  
200-kg net plastic drums.  
1000-kg net plastic drums.

**FLUOFAX YELLOW**  
**AMARILLA FLUORESCENTE**

**TECHNICAL CHARACTERISTICS / CARACTERISTICAS TECNICAS**

| Colour ref. No:  | FLUOFAX YELLOW |  |  |
|--|----------------|--|--|
| Specific Gravity   | 1,05 ± 0,05    |  |  |
| pH   | 10,5 ± 1       |  |  |
| BROOKFIELD Viscosity SC4-18 200 RPM 60"<br>(cps at 25°C) | 3 +/- 0,5      |  |  |
| SURFACE TENSION m N/m                                    | 38 +/-5        |  |  |
|  |                |  |  |
|  |                |  |  |
|  |                |  |  |

**HANDLING INSTRUCTIONS / CONDICIONES DE UTILIZO**

Store between 15°C and 35°C

Do not expose to temperatures lower than 5°C and higher than 35°C

**PACKING / CONFECCION**

5-kg net plastic drums.  
10-kg net plastic drums.  
20-kg net plastic drums.  
50-kg net plastic drums.  
200-kg net plastic drums.  
1000-kg net plastic drums.



## Scheda Tecnica Technical Data Sheet Ficha Tecnica

### NEUTRAL FLUORESCENT NEUTRA FLUORESCENTE

| TECHNICAL CHARACTERISTICS / CARACTERISTICAS TECNICAS     |                     |  |  |
|--|---------------------|--|--|
| Colour ref. No:  | Neutral Fluorescent |  |  |
| Specific Gravity   | 1,05 ± 0,05         |  |  |
| pH   | 9,5 ± 1             |  |  |
| BROOKFIELD Viscosity SC4-18 200 RPM 60"<br>(cps at 25°C) | 3 +/- 0,5           |  |  |
| SURFACE TENSION m N/m                                    | 33 +/-5             |  |  |
|  |                     |  |  |
|  |                     |  |  |
|  |                     |  |  |

#### HANDLING INSTRUCTIONS / CONDICIONES DE UTILIZO

Store between 15°C and 35°C

Do not expose to temperatures lower than 5°C and higher than 35°C

#### PACKING / CONFECCION

5-kg net plastic drums.  
10-kg net plastic drums.  
20-kg net plastic drums.  
50-kg net plastic drums.  
200-kg net plastic drums.  
1000-kg net plastic drums.